

3,500 lb Capacity Roller Conveyor

This medium-duty roller conveyor is the perfect solution for many assembly and warehouse application requirements. Available in non-powered, chain driven live roller, and zero pressure accumulation models.

Our rugged 1.9" roll diameter roller conveyor is designed to handle up to 3,500 lb loads and is easy to layout, install, and maintain.

We also offer a full line of medium-duty accessory equipment, such as: chain transfers, turntables, stops and curves, in addition to our heavy load handling systems with load capacities up to 20,000 lb.



Specification	Description
Model:	Chain Driven Live Roller - CDLR-1916-7G-40 or 50 chain Pallet Accumulation - PAC-1916-7G-40 or 50 chain Gravity -GRC-1916-7G
Frame:	5-1/2" x 2" 10 Gauge Formed Steel Channels
Roller Tube:	1.9" Diameter/16 Gauge Steel
Axle:	7/16" Hex Spindle - Spring Loaded
Roller Bearings:	Sealed & Grease Packed
Roller Capacity:	Up to 240 lb Per Roll
Roll Center:	3, 4, or 6 Inches On Center
Roll-to-Roll Drive:	ANSI RC 40 or 50 Chain (CDLR & PAC)
Roll Set:	High or Low
Length:	Increments of Roll Centers to 20"
Effective Width:	7 to 59 Inches in 3" Increments
Overall Width:	7-1/2 Inches Greater Than The Effective Width (CDLR & PAC) 4 Inches Greater Than The Effective Width (GRC)
Drive:	Inboard/Underslung or Direct Drive (CDLR and PAC)
Paint:	Webb Standard Blue
Connectors:	Butt Couplings

For Further Information, Please Contact:

ISO 9001 34375 W. Twelve Mile Road
CERTIFIED Farmington Hills, MI 48331 USA
 Phone: 1-248-553-1220 FAX: 1-248-553-1228
 www.jervisbwebb.com
 Bulletin NO. 5065-020304 © 2002 Jervis B. Webb Company

Jervis B. Webb Company
 MATERIAL HANDLING SYSTEM SPECIALISTS

